



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

**MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

NOTICE OF ACCEPTANCE (NOA)

Ergon Asphalt & Emulsions Inc.
450 Funston Road
Kansas City, Kansas 66115

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Blackhawk Cements and Coatings

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This renews NOA 09-0428.07 and consists of pages 1 through 4.
The submitted documentation was reviewed by Juan E. Collao, R.A.



NOA No.: 14-0505.05
Expiration Date: 05/28/19
Approval Date: 12/11/14
Page 1 of 4

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cements-Adhesives-Coatings
Material: Asphalt

SCOPE:

This approves “**Blackhawk Cements and Coatings**” manufactured by Ergon Asphalt & Emulsions, Inc., as roof coatings, cements and adhesives as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, and the High Velocity Hurricane Zone of the Florida Building Code.

MANUFACTURING LOCATION:

1. Kansas City, KS

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Construction Materials	EATC-003-02-01	ASTM D 4479	04/08/09
Technologies, LLC	EATC-002-02-01	ASTM D 4586	04/08/09
	EATC-005-02-01	ASTM D 41	04/08/09
	EATC-001-02-01	ASTM D 4586	04/08/09

PHYSICAL PROPERTIES OF COMPONENTS:

Trade name: **Blackhawk Seal Kote Light (BH5500)**

Thickness: See Systems Approvals Below.

Specifications: ASTM D 4479

Description: Single component, asphalt adhesive designed for adhering modified bitumen membranes. Apply with a 1/4” serrated squeegee at an application rate of 1½ to 2 gal./100 ft². Used for protecting, waterproofing, patching and sealing old and new roofs.

Container Sizes: 1, 5, 55 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System’s Product Control Notice of Acceptance where it exceeds standards of this NOA.

Trade name: **Blackhawk Seal Kote Heavy (BH5600)**

Thickness: See Systems Approvals Below.

Specifications: ASTM D 4586

Description: Asbestos free, fiber-reinforced premium asphalt roof cement. Apply with trowel at a minimum thickness of 1/8” to 1/4”. Application rates are 14 ft²/gal at 1/8” thickness.

Container Sizes: 1, 5, 55 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System’s Product Control Notice of Acceptance where it exceeds standards of this NOA.

MIAMI-DADE COUNTY
APPROVED

NOA No.: 14-0505.05
Expiration Date: 05/28/19
Approval Date: 12/11/14
Page 2 of 4

Trade name: **Blackhawk Plastic Roof Cement (BH5400)**

Thickness: See Systems Approvals Below.

Specifications: ASTM D 4586

Description: Asbestos free, fiber reinforced, asphalt roofing cement. Apply with trowel at a minimum thickness of $\frac{1}{8}$ " to $\frac{1}{4}$ ". Application rates are 14 ft²/gal at $\frac{1}{8}$ " thickness. Used for protecting, waterproofing, patching and sealing old and new roofs.

Container Sizes: 1, 5, 55 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Trade name: **Blackhawk Primer (BH5103)**

Thickness: See Systems Approvals Below.

Specifications: ASTM D 41

Description: Asphalt-solvent blend primer used on porous or rough surfaces. Apply at a rate of $\frac{1}{2}$ - $\frac{3}{4}$ gal/100 ft².

Note: Not to be used for APP modified bitumen cap sheet torch applied products with polyethylene backing

Container Sizes: 1, 5, 55 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.



BUILDING PERMIT REQUIREMENTS:

Application for building permit shall be accompanied by copies of the following:

1. This Notice of Acceptance
2. Any other documents required by the building official or the applicable building code in order to properly evaluate the installation of this system.

LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
2. Ergon Asphalt & Emulsions, Inc., products listed herein shall not be applied in inclement weather conditions.
3. Ergon Asphalt & Emulsions, Inc., products listed herein may not be applied over asphaltic shingles, metal shingles, fiber-cement shingles, wood shingles, quarry slate, cement or clay roofing tile or wood shakes.
4. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance. See roof system Notice of Acceptance for application rates and uses.
5. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami Dade Product Control upon request.
6. Change in materials, use, or manufacture of any products listed herein shall be cause for termination of this Notice of Acceptance.
7. Ergon Asphalt & Emulsions, Inc., products listed herein shall be applied in accordance with manufacturer's published application instructions unless specified otherwise within Notice of Acceptance approvals.
8. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
9. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF ACCEPTANCE



NOA No.: 14-0505.05
Expiration Date: 05/28/19
Approval Date: 12/11/14
Page 4 of 4